

MODEL	PART No.	VOLT	MAX AMP	MAX INLET	MAX HEAD	MAX DELIVERY
<i>U020-12</i>	64809 R	12V DC	26 A	4 m (13.1')	10 m (32.8')	28 l/min
<i>U020-24</i>	64812 D	24V DC	14 A	4 m (13.1')	10 m (32.8')	28 l/min
<i>U025-12</i>	64810 Z	12V DC	38 A	6 m (19.7')	12 m (39.4')	52 l/min
<i>U025-24</i>	64813 F	24V DC	22 A	6 m (19.7')	12 m (39.4')	52 l/min
<i>U030-12</i>	64811 B	12V DC	40A	6 m (19.7')	18 m (59.0')	75 l/min
<i>U030-24</i>	64814 H	24V DC	24 A	6 m (19.7')	18 m (59.0')	75 l/min
<i>U040</i>	64815 K	24 V DC	45 A	6 m (19.7')	22 m (72.2')	120 l/min
<i>U050-M</i>	66329 L	230V AC	12 A	6 m (19.7')	30 m (98.4')	230 l/min
<i>U050-T</i>	66330 V	380V AC	7,6 ÷ 4,4 A	6 m (19.7')	30 m (98.4')	230 l/min
<i>U050</i>	23610 J	24 V DC	96 A	6 m (19.7')	30 m (98.4')	230 l/min
<i>U070-T</i>	66331 X	380V AC	11,8 A	6 m (19.7')	40 m (131.2')	500 l/min