

<b>INSTRUMENT</b>	<b>HOLE SIZE mm (")</b>	<b>DIAL RANGE</b>	<b>DESCRIPTION</b>	<b>DRESS WHITE PART No.</b>
Tachometer/hourmeter	85 (3.35)	4000 RPM	Tachometer 4000 1/10 speed ratio*	62658 KK
	85 (3.35)	4000 RPM	Tachometer 4000 0,5/250 speed ratio**	22502 AK
	85 (3.35)	6000 RPM	Tachometer 6000 1/10 speed ratio*	62656 FK
	85 (3.35)	6000 RPM	Tachometer 6000 0,5/250 speed ratio**	22503 CK
	85 (3.35)	8000 RPM	Tachometer 8000 1/10 speed ratio*	22504 EK
	85 (3.35)	8000 RPM	Tachometer 8000 0,5/250 speed ratio**	22505 GK
Speedometer	85 (3.35)	35 Knots	Pitot tube provides pressure signals (not included)	22506 JK
	85 (3.35)	55 Knots		22508 NK
	85 (3.35)	65 Knots		22507 LK
	85 (3.35)	60 Knots GPS	GPS signal (antenna included)	22509 RK
Fuel level gauge	52 (2.05)	E - 1/2 - F	0-190 ohm	62664 EK
Water level gauge	52 (2.05)	E - 1/2 - F	0-190 ohm	62665 GK
Holding tank level gauge	52 (2.05)	E - 1/2 - F	240-33 ohm	22501 YK
Oil pressure gauge	52 (2.05)	0 - 5 bar	Pressure sensors provide signals (not included)	62666 JK
	52 (2.05)	0 - 10 bar		62667 LK
Exhaust temperature gauge	52 (2.05)	0 - 800°C	Exhaust temperature sensor provides signal (not included)	22510 ZK
Clock	52 (2.05)	-	Analog	62676 MK
Ammeter	52 (2.05)	± 80 A	Matched with 100 A current shunt unit (included)	22511 BK
Water temperature gauge	52 (2.05)	40 - 120 °C	Temperature sensor provides signals (not included)	62669 RK
Hourmeter	52 (2.05)	0 - 99999 hours	-	62672 DK
Trim gauge	52 (2.05)	160-10 ohm	Requires sending unit on outboard or sterndrive (check resistance values)	22512 DK
	52 (2.05)	0-190 ohm		22513 FK
Rudder angle indicator	85 (3.35)	Port-Starboard	Indicates relative position of rudder	62678 SK
Voltmeter	52 (2.05)	8-16 Volt	For all 12 Volt electrical system For all 24 Volt electrical system	62670 ZK
	52 (2.05)	18-32 Volt		62671BK