

RITCHIE® MODEL	UFLEX® PART No.	DIAL APP. Ø	MOUNT	BOAT TYPE	DIAL READING	NIGHT LIGHTING	COMPENSATORS	WEIGHT
<i>SP-5B</i>	67329 S	5"	binnacle	power/sail	flat-card	12V/24V green	built-in	2720 g - 6 lbs
<i>SP-5C</i>	67328 P	5"	binnacle	power/sail	flat-card	12V/24V green	built-in	2720 g - 6 lbs
<i>D-515-EP</i>	67396 H	5"	binnacle	power/sail	flat-card	12V/24V green	built-in	4540 g - 10 lbs
<i>D-515-X</i>	67397 K	5"	binnacle	power/sail	flat-card	12V/24V green	built-in	4540 g - 10 lbs
<i>FB-500</i>	67398 M	5"	flush	power/sail	flat-card	12V/24V green	built-in	2610 g - 5 lbs
<i>SS-5000 SUPERSPORT</i>	67399 P	5"	flush	high perform. power	powerdamp + flat-card dial	12V/24V green	built-in	2610 g - 5 lbs
<i>SS-5000W SUPERSPORT</i>	67400 V	5"	flush	high perform. power	powerdamp + flat-card dial	12V/24V green	built-in	2610 g - 5 lbs

Voltage available on request: 32V

Optional protective cover GM-5-C 67401 X:
for SP-5 and D-515-EP compasses

Optional protective cover LL-C 67402 Z:
for FB-500 and SS-5000

Weather shield WS-P (optional) 67403 B:
for SP-5 and D-515-EP

All Globemaster® compasses are individually custom assembled to order.
When ordering a Globemaster® compass it is important to specify your choice of power or sailboat model; 2°, 2° w/points, or 5° dial; 12, 24, or 32-volt night lighting and your choice of Polished Stainless (P), Black (B) or Polished Brass (X) finish on all models.