

PROSTAR™ SERIES TECHNICAL SPECIFICATIONS

MODEL	PS15M	PS30M	PS15M-48V
Part No.	62643W	61737A	63072H
Nominal Voltage	12V DC	24V DC	48V DC
Rated solar current	15 Amp	30 Amp	15 Amp
Rated load current	15 Amp	30 Amp	15 Amp
Load disconnect/LVD reconnect	11,5 V/12,6V	11,5 V/12,6V	11,5 V/12,6V
Self consumption	22 mA	22 mA	28 mA
Dimensions mm	153 x 105 x 55	153 x 105 x 55	153 x 105 x 55
Weight	0,34 kg	0,34 kg	0,34 kg

SUNSAVER™ SERIES TECHNICAL SPECIFICATIONS

MODEL	SS 6 L	SS 10	SS 10 L	SS 20 L	SS10 L-24
Part No.	61213E	61415B	61192X	61734U	61938L
Nominal Voltage	12V DC	12V DC	12V DC	12V DC	24V DC
Rated solar current	6 A	10 A	10 A	20 A	10 A
Rated load current	6 A	10 A	10 A	20 A	10 A
Load disconnect/LVD reconnect	11,5 /12,6V	11,5 /12,6V	11,5 /12,6V	11,5 /12,6V	23/25,2V
LVD reconnect	Yes	No	Yes	Yes	Yes
Dimensions mm	152x55x34	152x55x34	152x55x34	152x55x34	152x55x34
Weight	0,23 kg	0,23 kg	0,23 kg	0,23 kg	0,23 kg