

MODEL	PART No.	VOLT	MAX AMP	MAX INLET	MAX HEAD	MAX DELIVERY
UABR 32/1	66068 J	24V DC	52 A	9 m (29.5')	28 m (82')	160 l/min
UABR 32/2	66069 L	24V DC	90 A	9 m (29.5')	52 m (164')	160 l/min
UABR 40/1	66070 V	24V DC	90 A	9 m (29.5')	40 m (114.8')	250 l/min
UABR 32/1-M	67948 X	230V AC	9,6 A	9 m (29.5')	25 m (82')	150 l/min
UABR 32/1-T	67949 Z	380V AC	4,8 ÷ 2,7 A	9 m (29.5')	25 m (82')	150 l/min
UABR 32/2-M	66071 X	230V AC	12 A	9 m (29.5')	50 m (164')	150 l/min
UABR 32/2-T	66092 F	380V AC	7,7 ÷ 4,4 A	9 m (29.5')	50 m (164')	150 l/min
UABR 40/1-M	67950 H	230V AC	14 A	9 m (29.5')	38 m (124.7')	220 l/min
UABR 40/1-T	67951 K	380V AC	9 ÷ 5,2 A	9 m (29.5')	38 m (124.7')	220 l/min
UABR 40/2-T	66093 H	380V AC	15 ÷ 8,7 A	9 m (29.5')	75 m (236.2')	220 l/min
UABR 50/2-T	66073 B	380V AC	18,2 ÷ 10,2 A	9 m (29.5')	82 m (269')	400 l/min
UABR 65/2-T	66074 D	380V AC	29 ÷ 16 A	9 m (29.5')	85 m (278.8')	600 l/min